



## A Series 500 550 600

The ideal family boat for every occasion

### Standard Features

Hypatex 2-tone blue and light grey tubes, with 6 grab handles, moulded lifeline holders, lifelines, wear patches, dual rubbing strake

Bow fairlead on GRP moulding with stainless steel cleat

Deep V hull, monocoque construction with moulded deck

Splashwell including drains, hull drains

Integral sculpted rear seat with large storage area

Bow eye, 2 transom U bolts, anchor eye

100 litres underdeck fuel tank (500 & 550)

120 litres underdeck fuel tank (600)

Bow seat with cushion and locker beneath

Odyssey console with front seat and storage (500, 550, 600)

2 x 2-man jockey seats (600)

2 x 1-man jockey seats (500, 550)

Steering wheel, helm

Owner's manual

### Accessories

Odyssey console without front seat

Teak decking

1-man jockey seat - all models

Backrests for sculpted rear seat

Swing back helm seat

Bimini cover

Mooring cover

Boarding platform with telescopic ladder

A-frame with navigation lights

Hydraulic steering

500



550



600



### Technical Specifications

	500	550	600
Overall Length	5.00m	5.50m	6.00m
Internal Length	4.05m	4.55m	5.05m
Overall Width	2.28m	2.28m	2.28m
Inside Width	1.38m	1.38m	1.38m
Tube Diameter	0.46m	0.46m	0.46m
Number of Air Chambers	5	5	5
Number of Persons	8	10	12
Maximum Payload	765kg	1000kg	1100kg
Boat Weight Std Spec	410kg	450kg	520kg
Maximum Power	80hp	100hp	120hp
Engine Shaft	L	L	L
Design Category	C	B	B
Boat Weight inc Eng/Rigging	762kg	805kg	916kg
Boat & Trailer Weight	1102kg	1150kg	1261kg
Trailer Weight	340kg	345kg	345kg
Height on Trailer	2.35m	2.35m	2.35m
Height of Boat	1.80m	1.80m	1.80m
Engine Weight	170kg	170kg	200kg
Prop Size	17"	19"	19"
Draft in Water at Rest	0.47m	0.47m	0.47m
Max Speed	32knts	35knts	40knts

Ribeye carries out a continuous program of product improvement and safety awareness. Specifications are subject to change without notice, although all details are correct at the time of going to press. Ribeye products may be produced with a different trim level than originally specified. All dimensions are +/- 3%.

Please note that performance of your boat depends on engine size, propeller selection, trim settings, payload distribution and operating conditions. Refer to sections within this manual and within your engine owner's manual to obtain the best performance from your Ribeye.

Ribeye Ltd, Collingwood Road, Townstal, Dartmouth, Devon TQ6 9JY

E: sales@ribeye.co.uk T: 01803 832060 F: 01803 839090

Powered by  **YAMAHA**





### Standard Rigging for A Series

- Control box flush mounted on side
- Ignition switch panel & lanyard (kill cord)
- Hydraulic steering (F115 as standard)
- Fuel filter & connector
- Chrome transom bracket
- Rigging grommets
- 4-Stroke oil 10w40 5ltrs
- Ultraflex ST cables
- TFXtreme remote control cables
- Battery & battery box
- Bilge pump
- Bilge pump switch
- Ribeye switch panel
- Hull bungs
- Engine nutlock
- Ribeye repair kit & hand pump

### Trailers

Ribeye trailers are available for the full range of Ribeye boats, and are set up specifically to aid launch and recovery.

The following comes as standard:

- Rod operated brakes
- Lighting board
- Multi-roller launch and recovery
- Hub & brake flush facility
- Hitch lock

### Electronics

We fit Garmin as our chosen electronics. Fitted to the A Series are the GPSmap 551s & 100i VHF.

The GPSmap 551s combines chartplotter and fishfinder into one compact unit. Preloaded with charts to cover the whole of UK and Ireland (inc North coast of France). With a built-in GPS antenna, the 551s offers class leading ease of use. It has a 5" sunlight readable display which can be split to display both charts and fishfinder at the same time. This product has full integration with the 100i VHF features.

### Yamaha

Yamaha lead the world in high performance marine engines. Their range of four stroke outboards is the most complete line-up of engines offering performance, reliability and durability.

Engine models used in A Series Range:

- F115
- F100
- F80
- F70
- F60

