

RIBEYE T SERIES

THE PERFECT LANDING CRAFT

Ribeye Tenders are ideally suitable for beaching roles, typical for long-term tender use. Such smaller boats are much more likely to be dragged onto beaches or slipways where gravel, shingle and hard surfaces can be less than friendly to GRP hulls, which can be prone to deep scratching and the wear & tear of frequent abrasion. Aluminium hulls will take the punishment year after year.

Ribeye all-aluminium tenders are roomy, strong and robust, yet light and easy to transport. The smaller models travel easily on roof rack, swim platform or coach roof; however all models can be davit hung or towed astern.

Because of their light weight they are a real alternative for those who may have chosen an inflatable in the past for getting to and from a larger boat but would prefer a hard hull.

Tiller steering is standard on all models but an attractive range of consoles can be fitted for use with higher hp for remote use.



Tender Light					Tender Standard					Tender All-Aluminium					
TL Model	240	260	280	310	TS Model	280	310	350	370	TA Model	350	365	400	430	480
Standard Features					Standard Features					Standard Features					
Hypatex 2-tone white and light grey tubes with 5 grab handles and 4 fabric handles (8 fabric handles on 310), white epoxy powder coated all-aluminium hulls, removable plastic thwart seat, 2 inside handles for additional seat Heavy duty rubbing strake and heavy duty keel rubbing strake Removable lock-in rowlocks, aluminium oars, auto-bailing transom drains Internal oar storage, davit lifting points, repair kit, foot pump					Hypatex 2-tone white and light grey tubes with 5 grab handles and 6 fabric handles (4 fabric handles on 280), white epoxy powder coated all-aluminium hulls Removable thwart seat with storage and cup holder, removable lock-in rowlocks Heavy duty rubbing strake & heavy duty keel rubbing strake, repair kit, foot pump 2 inside handles for additional seat, aluminium oars, auto-bailing transom drains Unique zip bow dodger, internal oar storage, davit lifting points, 3-point towing Integral raised floor including fuel tank securing strap, double fixing point on bow					Hypatex 2-tone white and light grey tubes with 4 grab handles and 6 fabric handles (4 fabric handles on 350 & 365), white epoxy powder coated all-aluminium hulls Anti-slip decktread, raised anchor locker with access hatch and mooring cleat 4 inside grab handles, auto-bailing transom drains, davit lifting points Double fixing point on bow, large diameter, multi-compartment buoyancy tubes Recessed inflation valves, bow cleat, heavy duty rubbing strake, foot pump Reinforced transoms to support up to 70hp outboard motor, repair kit					
Optional extras					Optional extras					Optional extras					
Dinghy wheels Snap davits					Dinghy wheels Snap davits Mini single jockey console					Single Jockey console Double Jockey console Deluxe console with helm seat, screen & rail, integral s/s fuel tank (43l) Standard console with helm seat, integral s/s fuel tank (35l) Oars					
					Weight 10kg					Weight 32kg Weight 43kg Weight 39kg Weight 30kg					
Technical Specifications					Technical Specifications					Technical Specifications:					
	TL 240	TL 260	TL 280	TL 310		TS 280	TS 310	TS 350	TS 370		TA 350	TA 365	TA 400	TA 430	TA 480
Overall Length	2.40m	2.60m	2.74m	3.10m	Overall Length	2.74m	3.10m	3.48m	3.70m	Overall Length	3.48m	3.65m	3.96m	4.27m	4.88m
Internal Length	1.61m	1.75m	1.89m	2.15m	Internal Length	1.89m	2.15m	2.47m	2.67m	Internal Length	2.47m	2.62m	2.85m	3.15m	4.11m
Overall Width	1.32m	1.42m	1.50m	1.65m	Overall Width	1.50m	1.65m	1.65m	1.65m	Overall Width	1.65m	1.65m	2.03m	2.03m	2.03m
Inside Width	0.58m	0.58m	0.66m	0.73m	Inside Width	0.66m	0.73m	0.73m	0.73m	Inside Width	0.73m	0.73m	1.00m	1.00m	1.00m
Tube Diameter	32cm	39cm	39cm	47cm	Tube Diameter	39cm	47cm	47cm	47cm	Tube Diameter	41cm	41cm	41cm	41cm	48mm
Number of Air Chambers	2	2	2	3	Number of Air Chambers	2	3	3	3	Number of Air Chambers	3	3	3	4	5
Number of Persons	3	4	5	5+1	Number of Persons	4+1	5	5	6	Number of Persons	5	5 + 1	7	8	9
Maximum Payload	270kg	360kg	450kg	540kg	Maximum Payload	450kg	540kg	630kg	660kg	Maximum Payload	630kg	660kg	680kg	720kg	810kg
Boat only Weight	29kg	33kg	35kg	43kg	Boat only Weight	45kg	55kg	58kg	62kg	Boat only Weight	80kg	108kg	116kg	120kg	186kg
Maximum Power	4	5	8	9.9	Maximum Power	9hp	15hp	25hp	25hp	Maximum Power	25hp	30hp	40hp	50hp	60hp
Engine Shaft	S	S	S	S	Engine Shaft	S	S	S	S	Engine Shaft	L	L	L	L	L
Design Category	C	C	C	C	Design Category	C	C	C	C	Design Category	C	C	C	C	C
Max Engine Weight	22kg	22kg	37kg	39kg	Max Engine Weight	37kg	52kg	62kg	62kg	Max Engine Weight	82kg	86kg	86kg	110kg	110kg